

U.S. Serial No.: 10/659,682

**CLAIMS**

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. An encoder apparatus for enabling a push dataflow bitstream without causing a modeled data buffer of predetermined memory size for the pushed data at a decoder to overflow or underflow, comprising:

a processor adapted to encode data to provide the bit-stream for communication to a decoder; wherein:

the encoded data comprises at least one video or visual object (VO) with at least one video or visual object layer (VOL), including an associated header, followed by at least one video or visual object plane (VOP);

a field in the VOL header designates an occupancy of the buffer just before removal of the first VOP following the VOL header from the buffer; and

said processor uses a simulation to simulate the decoder buffer and controls the bitstream in response to the simulation to preclude overflow or underflow of the decoder buffer.

2. The apparatus of claim 1, wherein:

when the buffer is initially empty, the occupancy field is examined to determine an initial occupancy of the buffer before decoding the initial VOP.

3. The apparatus of claim 1, wherein:

the processor provides a flag to control the inclusion of at least one field in the

U.S. Serial No.: 10/659,682

VOL header when equivalent information is not present in an encapsulating system multiplex.

4. The apparatus of claim 3, wherein:

the flag allows a visual elementary stream of the bitstream as a standalone entity to specify a buffer model.

5. The apparatus of claim 3, wherein:

the at least one field whose inclusion in the VOL header is controlled by the flag designates a VOP rate of the bitstream.

6. The apparatus of claim 3, wherein:

the at least one field whose inclusion in the VOL header is controlled by the flag designates a peak bit rate of the bitstream.

7. The apparatus of claim 3, wherein:

the at least one field whose inclusion in the VOL header is controlled by the flag designates whether the VOL contains at least one B- VOP.

8. The apparatus of claim 3, wherein:

the at least one field whose inclusion in the VOL header is controlled by the flag designates the size of the modeled buffer.

**BEST AVAILABLE COPY**

U.S. Serial No.: 10/659,682

9. The apparatus of claim 3, wherein:  
the at least one field whose inclusion in the VOL header is controlled by the flag designates said field that designates the occupancy of the buffer.
10. The apparatus of claim 1, wherein:  
the video or visual object comprises a video object.
11. The apparatus of claim 1, wherein:  
the video or visual object comprises a still texture object.
12. The apparatus of claim 1, wherein:  
the video or visual object comprises a mesh object.
13. The apparatus of claim 1, wherein:  
the video or visual object comprises a face object.
14. The apparatus of claim 1, wherein:  
the encoded data comprises a plurality of VOLs, and a decoder buffer model is applied independently to each VOL using buffer size and rate functions particular to each VOL.
15. The apparatus of claim 1, wherein:  
the bitstream is compatible with an MPEG-4 video coding standard.

U.S. Serial No.: 10/659,682

16. The apparatus of claim 1, wherein:

additional fields are provided in respective subsequent VOL headers to designate respective subsequent buffer occupancy levels.

17. The apparatus of claim 16, wherein:

the processor maintains a difference between the additional fields in the subsequent VOL headers and a running cumulative buffer occupancy just before removal of a VOP from the buffer within a tolerance.

18. The apparatus of claim 1, wherein:

the processor determines a size ( $d_i$ ) of a current VOP as a number of bits extending to the last bit of the current VOP and starting from either the last bit of the previous VO or the first bit of a start code for the first VOP of the encoded data.

19. The apparatus of claim 1, wherein:

the processor determines a decoding time  $t_i$  of an  $i$ th VOP, wherein:

(a)  $t_i = \tau_i$  if the VOL contains no B-VOPs, where  $\tau_i$  is a composition time of the  $i$ th VOP, and

(b)  $t_i = \tau_i + m_i$ , when the  $i$ th VOP is an anchor VOP, and  $m_i$  accounts for a delay of at least one immediately subsequent B-VOP to be composited or presented.

U.S. Serial No.: 10/659,682

20. The apparatus of claim 1, wherein:

the processor determines a decoding time  $t_i$  of an  $i$ th VOP, wherein:

(a)  $t_i = \tau_i$  if the VOL contains no B-VOPs, where  $\tau_i$  is a presentation time of the  $i$ th VOP when the decoder is a no-compositor decoder, and

(b)  $t_i = \tau_i - m_i$ , when the  $i$ th VOP is an anchor VOP, and  $m_i$  accounts for a delay of at least one immediately subsequent B-VOP to be composited or presented.

21. The apparatus of claim 1, wherein:

said pushed data flow comprises video data that includes intraframe (I), prediction (P) and bi-directional (B) video object planes (VOPs).

22. The apparatus of claim 21, wherein said processor controls said bitstream by at least one of: allocating bits between different VOPs, and adjusting quantization levels of coding units forming said VOPs.

23. The apparatus of claim 22, wherein:

the modeled data buffer comprises a visual or video buffering verifier (VBV) buffer.

24. The apparatus of claim 23, wherein:

said processor monitors the VBV buffer and, when the simulation indicates that

U.S. Serial No.: 10/659,682

the VBV buffer has or will become too full, a quantization level for said coding units is reduced.

25. The apparatus of claim 23, wherein:

said processor monitors the VBV buffer and, when the simulation indicates that the VBV buffer has or will become too empty, said quantization level for said coding units is increased.

26. The apparatus of claim 23, wherein:

said processor monitors the VBV buffer and, when the simulation indicates that the VBV buffer has or will become too empty, the generation of the next VOP is delayed.

27. The apparatus of claim 23, wherein:

said processor monitors the VBV buffer and, when the simulation indicates that the VBV buffer has or will become too empty, high frequency coefficients of said coding units are zeroed to reduce the number of bits generated per VOP.

28. The apparatus of claim 23, wherein:

said processor monitors the VBV buffer and, when it is determined that the VBV buffer has or will become too full, stuffing bits are added to the end of at least one VOP.

29. The apparatus of claim 1, wherein:

the processor includes an encoder buffer for receiving the encoded data prior to

U.S. Serial No.: 10/659,682

providing the bitstream therefrom; and

the processor controls the rate of the bitstream such that the fullness of the encoder buffer  $eb_i^e$  after encoding an  $i$ th VOP is upper bounded by

$$\int_{t_i^e}^{t_i^e + L} R_{vol,encoder}(t) dt - d_i$$

where  $t_i^e$  is the time of starting to encode the  $i$ th VOP,  $L$  is the time difference between the encoding time  $t_i^e$  and the decoding time of the  $i$ th VOP,  $d_i$  is the amount of coded data for the  $i$ th VOP, and  $R_{vol,encoder}(t)$  is the instantaneous channel bit rate seen by the decoder.

30. The apparatus of claim 1, wherein:

the processor includes an encoder buffer for receiving the encoded data prior to providing the bitstream therefrom; and

the processor controls the rate of the bitstream such that the fullness of the encoder buffer  $eb_i^e$  after encoding an  $i$ th VOP is upper bounded by

$$\int_{t_i^e - L}^{t_i^e} R_{vol,encoder}(t) dt - d_i$$

U.S. Serial No.: 10/659,682

where  $t_i^e$  is the time of starting to encode the  $i$ th VOP,  $L$  is the time difference between the encoding time  $t_i^e$  and the decoding time of the  $i$ th VOP,  $d_i$  is the amount of coded data for the  $i$ th VOP, and  $R_{vol,encoder}(t)$  is the instantaneous channel bit rate seen by the encoder.

31. The apparatus of claim 1, wherein:

the processor includes an encoder buffer for receiving the encoded data prior to providing the bitstream therefrom; and

the processor controls the rate of the bitstream such that the fullness of the encoder buffer  $cb_i^e$  after encoding an  $i$ th VOP is lower bounded by

$$t_i^e + \int_{t_i^e}^{t_i^e + L} R_{vol,encoder}(t) dt - B,$$

where  $t_i^e$  is the time of starting to encode the  $i$ th VOP,  $L$  is the time difference between the encoding time  $t_i^e$  and the decoding time of the  $i$ th VOP,  $B$  is the size of the decoder buffer, and  $R_{vol,encoder}(t)$  is the instantaneous channel bit rate seen by the decoder.

32. The apparatus of claim 1, wherein:



U.S. Serial No.: 10/659,682

the processor includes an encoder buffer for receiving the encoded data prior to providing the bitstream therefrom; and the processor controls the rate of the bitstream such that the fullness of the encoder buffer  $eb_i^e$  after encoding an  $i$ th VOP is lower bounded by

$$\int_{t_i^e - L}^{t_i^e} R_{vol,encoder}(t) dt - B,$$

where  $t_i^e$  is the time of starting to encode the  $i$ th VOP,  $L$  is the time difference between the encoding time  $t_i^e$  and the decoding time of the  $i$ th VOP,  $B$  is the size of the decoder buffer, and  $R_{vol,encoder}(t)$  is the instantaneous channel bit rate seen by the encoder.

33. An encoding method for enabling a push dataflow bitstream without causing a modeled data buffer of predetermined memory size for the pushed data at a decoder to overflow or underflow, comprising the steps of:

encoding data to provide the bitstream for communication to a decoder; wherein:

the encoded data comprises at least one video or visual object (VO) with at least one video or visual object layer (VOL), including an associated header, followed by at least one video or visual object plane (VOP); and

a field in the VOL header designates an occupancy of the buffer just before removal of the first VOP following the VOL header from the buffer; and using a simulation to simulate the decoder buffer and control the bitstream in

U.S. Serial No.: 10/659,682

response to the simulation to preclude overflow or underflow of the decoder buffer.

34. The method of claim 33, wherein:

when the buffer is initially empty, the occupancy field is examined to determine an initial occupancy of the buffer before decoding the initial VOP.

35. The method of claim 33, comprising the further step of:

providing a flag to control the inclusion of at least one field in the VOL header when equivalent information is not present in an encapsulating system multiplex.

36. The method of claim 35, wherein:

the flag allows a visual elementary stream of the bitstream as a standalone entity to specify a buffer model.

37. The method of claim 35, wherein:

the at least one field whose inclusion in the VOL header is controlled by the flag designates a VOP rate of the bitstream.

38. The method of claim 35, wherein:

the at least one field whose inclusion in the VOL header is controlled by the flag designates a peak bit rate of the bitstream.

39. The method of claim 35, wherein:

U.S. Serial No.: 10/659,682

the at least one field whose inclusion in the VOL header is controlled by the flag designates whether the VOL contains at least one B-VOP.

40. The method of claim 35, wherein:

the at least one field whose inclusion in the VOL header is controlled by the flag designates the size of the modeled buffer.

41. The method of claim 35, wherein:

the at least one field whose inclusion in the VOL header is controlled by the flag designates said field that designates the occupancy of the buffer.

42. The method of claim 33, wherein:

the video or visual object comprises a video object.

43. The method of claim 33, wherein:

the video or visual object comprises a still texture object.

44. The method of claim 33, wherein:

the video or visual object comprises a mesh object.

45. The method of claim 33, wherein:

the video or visual object comprises a face object.

**BEST AVAILABLE COPY**

U.S. Serial No.: 10/659,682

46. The method of claim 33, wherein:  
the encoded data comprises a plurality of VOLs, and a decoder buffer model is applied independently to each VOL using buffer size and rate functions particular to each VOL.
47. The method of claim 33, wherein:  
the bitstream is compatible with an MPEG-4 video coding standard.
48. The method of claim 33, wherein:  
additional fields are provided in respective subsequent VOL headers to designate respective subsequent buffer occupancy levels.
49. The method of claim 48, comprising the further step of:  
maintaining a difference between the additional fields in the subsequent VOL headers and a running cumulative buffer occupancy just before removal of a VOP from the buffer within a tolerance.
50. The method of claim 33, comprising the further step of:  
determining a size ( $d_i$ ) of a current VOP as a number of bits extending to the last bit of the current VOP and starting from either the last bit of the previous VO or the first bit of a start code for the first VOP of the encoded data.
51. The method of claim 33, comprising the further step of:

U.S. Serial No.: 10/659,682

determining a decoding time  $t_i$  of an  $i$ th VOP, wherein:

(a)  $t_i = \tau_i$  if the VOL contains no B-VOPs, where  $\tau_i$  is a composition time of the  $i$ th VOP, and

(b)  $t_i = \tau_i - m_i$ , when the  $i$ th VOP is an anchor VOP, and  $m_i$  accounts for a delay of at least one immediately subsequent B-VOP to be composited or presented.

52. The method of claim 33, comprising the further step of:

determining a decoding time  $t_i$  of an  $i$ th VOP, wherein:

(a)  $t_i = \tau_i$  if the VOL contains no B-VOPs, where  $\tau_i$  is a presentation time of the  $i$ th VOP when the decoder is a no-compositor decoder, and

(b)  $t_i = \tau_i - m_i$ , when the  $i$ th VOP is an anchor VOP, and  $m_i$  accounts for a delay of at least one immediately subsequent B-VOP to be composited or presented.

53. The method of claim 33, wherein:

said pushed data flow comprises video data that includes intraframe (I), prediction (P) and bi-directional (B) video object planes (VOPs).

54. The method of claim 53, comprising the further step of controlling said bitstream by at least one of: allocating bits between different VOPs, and adjusting quantization levels of coding units forming said VOPs.

U.S. Serial No.: 10/659,682

55. The method of claim 54, wherein:  
the modeled data buffer comprises a visual or video buffering verifier (VBV) buffer.
56. The method of claim 55, comprising the further step of:  
monitoring the VBV buffer and, when the simulation indicates that the VBV buffer has or will become too full, reducing a quantization level for said coding units.
57. The method of claim 55, comprising the further step of:  
monitoring the VBV buffer and, when the simulation indicates that the VBV buffer has or will become too empty, increasing a quantization level for said coding units.
58. The method of claim 55, comprising the further step of:  
monitoring the VBV buffer and, when the simulation indicates that the VBV buffer has or will become too empty, delaying the generation of the next VOP.
59. The method of claim 55, comprising the further step of:  
monitoring the VBV buffer and, when the simulation indicates that the VBV buffer has or will become too empty, zeroing high frequency coefficients of said coding units to reduce the number of bits generated per VOP.
60. The method of claim 55, comprising the further step of:  
monitoring the VBV buffer and, when it is determined that the VBV buffer has or

U.S. Serial No.: 10/659,682

will become too full, adding stuffing bits to the end of at least one VOP.

61. The method of claim 33, wherein an encoder buffer receives the encoded data prior to providing the bitstream therefrom, comprising the further step of:

controlling the rate of the bitstream such that the fullness of the encoder buffer  $eb_i^e$  after encoding an  $i$ th VOP is upper bounded by

$$\int_{t_i^e}^{t_i^e + L} R_{vol,encoder}(t) dt - d_i$$

where  $t_i^e$  is the time of starting to encode the  $i$ th VOP,  $L$  is the time difference between the encoding time  $t_i^e$  and the decoding time of the  $i$ th VOP,  $d_i$  is the amount of coded data for the  $i$ th VOP, and  $R_{vol,encoder}(t)$  is the instantaneous channel bit rate seen by the decoder.

62. The method of claim 33, wherein an encoder buffer receives the encoded data prior to providing the bitstream therefrom, comprising the further step of:

controlling the rate of the bitstream such that the fullness of the encoder buffer  $eb_i^e$  after encoding an  $i$ th VOP is upper bounded by

$$\int_{t_i^e} R_{vol,encoder}(t) dt - d_i$$

U.S. Serial No.: 10/659,682

$$t_i^e - L$$

where  $t_i^e$  is the time of starting to encode the  $i$ th VOP,  $L$  is the time difference between the encoding time  $t_i^e$  and the decoding time of the  $i$ th VOP,  $d_i$  is the amount of coded data for the  $i$ th VOP, and  $R_{vol,encoder}(t)$  is the instantaneous channel bit rate seen by the encoder.

63. The method of claim 33, wherein an encoder buffer receives the encoded data prior to providing the bitstream therefrom, comprising the further step of:

controlling the rate of the bitstream such that the fullness of the encoder buffer  $eb_i^e$  after encoding an  $i$ th VOP is lower bounded by

$$\int_{t_i^e}^{t_i^e + L} R_{vol,encoder}(t) dt - B,$$

where  $t_i^e$  is the time of starting to encode the  $i$ th VOP,  $L$  is the time difference between the encoding time  $t_i^e$  and the decoding time of the  $i$ th VOP,  $B$  is the size of the decoder buffer, and  $R_{vol,encoder}(t)$  is the instantaneous channel bit rate seen by the decoder.

64. The method of claim 33, wherein an encoder buffer receives the encoded data



U.S. Serial No.: 10/659,682

prior to providing the bitstream therefrom, comprising the further step of:

controlling the rate of the bitstream such that the fullness of the encoder buffer  $eb_i^e$  after encoding an  $i$ th VOP is lower bounded by

$$\int_{t_i^e - L}^{t_i^e} R_{vol, encoder}(t) dt - B,$$

where  $t_i^e$  is the time of starting to encode the  $i$ th y p,  $L$  is the time difference between the encoding time  $t_i^e$  and the decoding time of the  $i$ th VOP,  $B$  is the size of the decoder buffer, and  $R_{vol, encoder}(t)$  is the instantaneous channel bit rate seen by the encoder.

65. A decoder apparatus, comprising:
- a data buffer of predetermined memory size; and
  - means for receiving a push dataflow bitstream that is obtained by encoding data in accordance with a model of the buffer so that the modeled buffer does not overflow or underflow; wherein:

the encoded data comprises at least one video or visual object (VO) with at least one video or visual object layer (VOL), including an associated header, followed by at least one video or visual object plane (VOP); and

a field in the VOL header designates an occupancy of the modeled buffer just before removal of the first VOP following the VOL header from the modeled buffer.

U.S. Serial No.: 10/659,682

66. The apparatus of claim 65, wherein:

the encoded data comprises a flag that controls the inclusion of at least one field in the VOL header when equivalent information is not present in an encapsulating system multiplex.

67. The apparatus of claim 66, wherein:

the flag allows a visual elementary stream of the bitstream as a standalone entity to specify a buffer model.

68. The apparatus of claim 66, wherein:

the at least one field whose inclusion in the VOL header is controlled by the flag designates a VOP rate of the bitstream.

69. The apparatus of claim 66, wherein:

the at least one field whose inclusion in the VOL header is controlled by the flag designates a peak bit rate of the bitstream.

70. The apparatus of claim 66, wherein:

the at least one field whose inclusion in the VOL header is controlled by the flag designates whether the VOL contains at least one B-VOP.

71. The apparatus of claim 66, wherein:

the at least one field whose inclusion in the VOL header is controlled by the flag

U.S. Serial No.: 10/659,682

designates the size of the modeled buffer.

72. The apparatus of claim 66, wherein:

the at least one field whose inclusion in the VOL header is controlled by the flag designates said field that designates the occupancy of the buffer.

73. The apparatus of claim 65, wherein:

the video or visual object comprises a video object.

74. The apparatus of claim 65, wherein:

the video or visual object comprises a still texture object.

75. The apparatus of claim 65, wherein:

the video or visual object comprises a mesh object.

76. The apparatus of claim 65, wherein:

the video or visual object comprises a face object.

77. The apparatus of claim 65, wherein:

the encoded data comprises a plurality of VOLs, and a decoder buffer model is applied independently to each VOL using buffer size and rate functions particular to each VOL.

U.S. Serial No.: 10/659,682

78. The apparatus of claim 65, wherein:  
the bitstream is compatible with an MPEG-4 video coding standard.
79. The apparatus of claim 65, wherein:  
additional fields are provided in respective subsequent VOL headers to designate  
respective subsequent buffer occupancy levels.
80. The apparatus of claim 65, wherein:  
said pushed data flow comprises video data that includes intraframe (I), prediction  
(P) and bi-directional (B) video object planes (VOPs).
81. A method for providing a push dataflow bitstream at a decoder, comprising the  
steps of:  
providing a data buffer of predetermined memory size at the decoder; and  
receiving the push dataflow bitstream at the decoder, wherein said bitstream is  
obtained by encoding data in accordance with a model of the buffer so that the modeled  
buffer does not overflow or underflow; wherein:  
the encoded data comprises at least one video or visual object (VO) with  
at least one video or visual object layer (VOL), including an associated header,  
followed by at least one video or visual object plane (VOP); and  
a field in the VOL header designates an occupancy of the modeled buffer  
just before removal of the first VOP following the VOL header from the modeled  
buffer.

U.S. Serial No.: 10/659,682

- 82. (Canceled)
- 83. (Canceled)
- 84. (Canceled)
- 85. (Canceled)
- 86. (Canceled)
- 87. (Canceled)
- 88. (Canceled)
- 89. (Canceled)
- 90. (Canceled)
- 91. (Canceled)
- 92. (Canceled)
- 93. (Canceled)
- 94. (Canceled)